

**Connector AM-TOP®** 

Part no. 525



screw terminals


•

- single part body cable gland and sealing strain relief and protection against kinking

## **Technical specifications**

| Ampere                    | 32 A            |
|---------------------------|-----------------|
| Poles                     | 4 p             |
| Voltage                   | 230 V           |
| Clock position            | 9 h             |
| Hertz                     | 50-60 Hz        |
| Connection technology     | Screw terminals |
| Contact                   | standard        |
| Protection type           | IP 44           |
| Weight                    | 331 g           |
| Declaration of Conformity | VDE, EAC, CQC   |

## Drawing



| Drawing                            | Amp.  |      | 16   |      |     | 32  |     |
|------------------------------------|-------|------|------|------|-----|-----|-----|
| 3 MB 63                            | Poles | 3    | 4    | 5    | 3   | 4   | 5   |
| Dim. in mm                         | а     | 162  | 165  | 167  | 209 | 209 | 208 |
|                                    | b     | 60   | 68   | 76   | 82  | 82  | 89  |
|                                    | h     | 83   | 92   | 98   | 100 | 100 | 108 |
|                                    | У     | 14.5 | 16   | 16   | 22  | 22  | 22  |
|                                    |       |      |      |      |     |     |     |
| Terminal for cond. cross           |       | 1    | 1    | 1    | 2.5 | 2.5 | 2.5 |
| section (mm <sup>2</sup> ) minmax. |       | -2.5 | -2.5 | -2.5 | —6  | —6  | —6  |