

Power post
Part no. 83722




- from steel tube
- wall thickness 4.5 mm
- hot-dip galvanised
- wet painted
- colour: anthracite
- iron glitter DB 703
- hinged supply aperture
- with safety lock
- dimensions (H x Ø): 1400 x 325 mm (inside)
- weight: approx. 100 kg
- aperture at bottom: (H x W) 50 x 100 mm
- fixing flange: Ø 450 mm
- with 4 fixing holes 15 mm
- for fixing to an existing fundament

Technical specifications

CEE 63 A, 5 p, 400 V	1
CEE 32 A, 5 p, 400 V	1
CEE 16 A, 5 p, 400 V	1
SCHUKO® 16 A, 230 V	2
Fusing	<ul style="list-style-type: none"> • 1 RCD 63 A, 4 p, 0.03 A • 1 MCB 32 A, 3 p, C • 1 MCB 16 A, 3 p, C • 2 MCB's 16 A, 1 p, B
Pre-fuse max.	63 A
InA	63 A
RDF	0.55
Connection / feeder cable	<ul style="list-style-type: none"> • for 2 cables up to 5 x 25 mm²
Protection type	IP 44
Shutter	false
Enclosure material	Metal
Weight	100000 g
Height	1400 mm
Diameter	325 mm
Declaration of Conformity	EAC

Drawing


Top view of the bottom plate



The supply aperture is located between 2 drill holes in the bottom plate

4 x Ø 15.5

Part no. 18502AZ
Colour: anthracite



Drawing
1 MB 445

Dim. in mm